

Network requirements	Values
Box Office /EBO / CRM / BI	
Network latency between operator machine and SecuTix datacenter	Max 50 ms
Bandwidth	Min 512 kbits/s (better = 1Mbit/s) per operator. Min 8 Mbit/s in download and min 1 Mb/s in upload.
Ports to open	The client must be able to contact the SecuTix servers on ports HTTPS (443) on the SecuTix Ranges: 193.73.238.0/24 + 193.72.147.0/24. All addresses of this range must be open.
SPF (Sender Policy Framework) Policy	<p>If the customer has a DNS / SPF Policy: Declare in the DNS/ SPF that the SecuTix servers (spf.secutix.com) are authorized to send e-mail to customers with the address (configured in SecuTix) For example ticketing@mytheater.com. This declares that the email sent from this DNS are valid and there won't be blocked as spam. Example of configuration of the DNS / SPF: ticketing@myteater.com. IN TXT "v=spf1 include:spf.secutix.com ~all"</p>
Access Control	
Network latency between operator machine and SecuTix datacenter	Max 50 ms
Wifi Dedicated Network	The network must be dedicated to access control (bandwidth not saturated) The network must have access to internet (To take control from SecuTix) Wifi Security: Min WPA
In case of turnstiles in SaaS mode, a VPN between SecuTix and the turnstiles is required	